

## Food industry accessories

### CDR.0300

**Spray gun, compensated blue,**  
inlet G 3/8" F, outlet G 1/4" F,  
350 bar  
5100 psi,  
30 l/min  
8.00 USGpm,  
160 °C  
320 °F



gr. 660  
oz. 23.3

### CDR.0070

**L.p. spray gun for big flow rate,**  
made of brass, inlet G 1/2" F,  
24 bar  
350 psi,  
100 l/min  
26.40 USGpm,  
90 °C  
195 °F



gr. 950  
oz. 33.6

### CDR.0065

**Swivel coupling, for l.p. spray gun, made of**  
brass, G 1/2" M-F,  
24 bar  
350 psi,  
100 l/min  
26.40 USGpm,  
90 °C  
195 °F



gr. 125  
oz. 4.5



Code	Length	Weight	Description
ZX.7124	700 mm 28"	gr. 490 oz. 17.3	<b>CdR® 80 moulded blue handle lance, with bend.</b> Made of stainless steel pipe, with nozzle holder coupling and protection.
ZX.7125	900 mm 36"	gr. 580 oz. 20.5	280 bar-4050 psi, 40 l/min-10.50 USGpm,
ZX.7126	1200 mm 47"	gr. 870 oz. 30.8	150 °C-300 °F.

H.p. hose R1 5/16"  
315 bar-4550 psi, BLUE

Code

Length  
m ft

Weight



G 3/8" F

G 3/8" F

ZB.CC080D2H2H	8 26.25	gr. 2540 oz. 88.9
ZB.CC100D2H2H	10 32.80	gr. 3090 oz. 108.2
ZB.CC150D2H2H	15 49.20	gr. 4460 oz. 156.1
ZB.CC200D2H2H	20 65.60	gr. 5840 oz. 204.4

With handles and stainless steel AISI 316 connections

H.p. hose R2 5/16"  
400 bar-5800 psi, BLUE

Code

Length  
m ft

Weight



G 3/8" F

G 3/8" F

ZB.DC080D2H2H	8 26.25	gr. 3990 oz. 139.7
ZB.DC100D2H2H	10 32.80	gr. 4900 oz. 171.5
ZB.DC150D2H2H	15 49.20	gr. 7170 oz. 251.0
ZB.DC200D2H2H	20 65.60	gr. 9450 oz. 330.8

With handles and stainless steel AISI 316 connections

## Ball valves

### TG.FT221138

**H.p. ball valve, 2 way,**  
made of zinc plated steel,  
G 3/8" F-F,  
500 bar  
7250 psi



gr. 650  
oz. 23.0

### TG.FT221112

**H.p. ball valve, 2 way,**  
made of zinc plated steel,  
G 1/2" F-F,  
500 bar  
7250 psi



gr. 750  
oz. 26.5

### EFF.2621X204

**H.p. ball valve, 2 way,**  
made of stainless steel  
AISI 316,  
G 1/2" F-F,  
100 bar  
1450 psi,  
80 l/min  
21.00 USGpm



gr. 650  
oz. 23.0

### EFF.26550203

**H.p. ball valve, 2 way,**  
made of stainless steel  
AISI 316,  
G 3/8" F-F,  
210 bar  
3050 psi,  
80 l/min  
21.00 USGpm



gr. 950  
oz. 33.6

### EFF.26550204

**H.p. ball valve, 2 way,**  
made of stainless steel  
AISI 316,  
G 1/2" F-F,  
210 bar  
3050 psi,  
80 l/min  
21.00 USGpm



gr. 950  
oz. 33.6

### H.p. ball valves



Code	Inlet	Outlet	Weight	Description
EFF.2321N203	G 3/8" F	G 3/8" F	gr. 500 oz. 17.5	<b>H.p. ball valves, made of brass, acetal resin h.p. seals and O-Ring in Viton.</b> 210 bar-3050 psi.
EFF.2321N204	G 1/2" F	G 1/2" F	gr. 650 oz. 22.8	
EFF.2321N205	G 3/4" F	G 3/4" F	gr. 1200 oz. 42.0	
EFF.2321N206	G 1" F	G 1" F	gr. 1550 oz. 54.3	