

Consumer items

- Self-centring blocking washers

ZX.0473

Box Dolly self-centring washers, made of steel with rubber vulcanized on internal diameter. In one solution 6 different size of washers.

In each box there are:

- no. 1 Set ZX.0475
- no. 1 Set ZX.0476
- no. 1 Set ZX.0477
- no. 1 Set ZX.0478
- no. 1 Set ZX.0479
- no. 1 Set ZX.0480

gr. 1450

oz. 51.2



Example:



Seal guaranteed even in delicate connections.

Self-centring washers



Code	Description	ø	Q.ty	Weight	Description
ZX.0475	Set Dolly RA 1/8	1/8"	50 pcs	gr. 80 oz. 2.9	It does not require centring.
ZX.0476	Set Dolly RA 1/4	1/4"	50 pcs	gr. 130 oz. 4.6	High eccentricity makes the seal steadier and reduces the assembly time.
ZX.0477	Set Dolly RA 3/8	3/8"	100 pcs	gr. 290 oz. 10.3	Ideal for connections, nipples, caps, etc.
ZX.0478	Set Dolly RA 1/2	1/2"	50 pcs	gr. 240 oz. 8.5	Temperature max. 90°C
ZX.0479	Set Dolly RA 3/4	3/4"	50 pcs	gr. 330 oz. 11.7	
ZX.0480	Set Dolly RA 1	1"	25 pcs	gr. 220 oz. 7.8	

Consumer items

- Copper washers

ZX.0474

Box Dolly copper washers, In one solution 6 different size of washers.

In each box there are:

- no. 1 Set ZX.0481
- no. 1 Set ZX.0482
- no. 1 Set ZX.0483
- no. 1 Set ZX.0484
- no. 1 Set ZX.0485
- no. 1 Set ZX.0486

gr. 1440

oz. 50.9



Example:



It removes the use of P.T.F.E and sealant


Copper washers








Code	Description	ø	Q.ty	Weight	Description
ZX.0481	Set Dolly RR 1/8	1/8"	100 pcs	gr. 155 oz. 5.5	Throwaway copper washers.
ZX.0482	Set Dolly RR 1/4	1/4"	100 pcs	gr. 190 oz. 6.8	Economic and ideal for connections, nipples, caps, etc.
ZX.0483	Set Dolly RR 3/8	3/8"	200 pcs	gr. 480 oz. 17.0	
ZX.0484	Set Dolly RR 1/2	1/2"	100 pcs	gr. 270 oz. 9.6	
ZX.0485	Set Dolly RR 3/4	3/4"	25 pcs	gr. 110 oz. 3.9	
ZX.0486	Set Dolly RR 1	1"	25 pcs	gr. 130 oz. 4.6	






Consumer items




- Threadlocking and threadsealing

<p>CDR.0848 Threadlocker 54-03, medium strength adhesive.</p> <p>For thread locking of nuts and bolts. Highly resistant to heat, corrosion, vibrations, water, gases, oils, hydrocarbons and many chemicals</p>  <table border="1"> <tr> <td>gr. 80</td> <td>50 ml</td> </tr> <tr> <td>oz. 2.9</td> <td>1.70 fl oz</td> </tr> </table>	gr. 80	50 ml	oz. 2.9	1.70 fl oz	<p>CDR.0849 Threadlocker 54-03, medium strength adhesive.</p> <p>For thread locking of nuts and bolts. Highly resistant to heat, corrosion, vibrations, water, gases, oils, hydrocarbons and many chemicals</p>  <table border="1"> <tr> <td>gr. 360</td> <td>250 ml</td> </tr> <tr> <td>oz. 12.7</td> <td>8.50 fl oz</td> </tr> </table>	gr. 360	250 ml	oz. 12.7	8.50 fl oz	<p>CDR.0850 Threadlocker 55-03, medium strength adhesive.</p> <p>For thread locking of nuts and bolts. Highly resistant to heat, corrosion, vibrations, water, gases, oils, hydrocarbons corrosion and many chemicals</p>  <table border="1"> <tr> <td>gr. 80</td> <td>50 ml</td> </tr> <tr> <td>oz. 2.9</td> <td>1.70 fl oz</td> </tr> </table>	gr. 80	50 ml	oz. 2.9	1.70 fl oz	<p>CDR.0851 Threadlocker 55-03, medium strength adhesive.</p> <p>For thread locking of nuts and bolts. Highly resistant to heat, corrosion, vibrations, water, gases, oils, hydrocarbons corrosion and many chemicals</p>  <table border="1"> <tr> <td>gr. 360</td> <td>250 ml</td> </tr> <tr> <td>oz. 12.7</td> <td>8.50 fl oz</td> </tr> </table>	gr. 360	250 ml	oz. 12.7	8.50 fl oz	<p>CDR.0852 Threadlocker 83-54, high strength adhesive.</p> <p>For locking and sealing of studs, nuts, bolts. Highly resistant to heat, corrosion, vibrations, water, gases, oils, hydrocarbons, and many chemicals</p>  <table border="1"> <tr> <td>gr. 80</td> <td>50 ml</td> </tr> <tr> <td>oz. 2.9</td> <td>1.70 fl oz</td> </tr> </table>	gr. 80	50 ml	oz. 2.9	1.70 fl oz
gr. 80	50 ml																							
oz. 2.9	1.70 fl oz																							
gr. 360	250 ml																							
oz. 12.7	8.50 fl oz																							
gr. 80	50 ml																							
oz. 2.9	1.70 fl oz																							
gr. 360	250 ml																							
oz. 12.7	8.50 fl oz																							
gr. 80	50 ml																							
oz. 2.9	1.70 fl oz																							

<p>CDR.0853 Threadlocker 83-54, high strength adhesive.</p> <p>For locking and sealing of studs, nuts, bolts. Highly resistant to heat, corrosion, vibrations, water, gases, oils, hydrocarbons, and many chemicals</p>  <table border="1"> <tr> <td>gr. 360</td> <td>250 ml</td> </tr> <tr> <td>oz. 12.7</td> <td>8.50 fl oz</td> </tr> </table>	gr. 360	250 ml	oz. 12.7	8.50 fl oz	<p>CDR.0863 Retaining+Sealant 83-21, high strength adhesive.</p> <p>For locking and sealing threads. Highly resistant to heat, corrosion, vibrations, water, gases, oils, hydrocarbons and many chemicals</p>  <table border="1"> <tr> <td>gr. 80</td> <td>50 ml</td> </tr> <tr> <td>oz. 2.9</td> <td>1.70 fl oz</td> </tr> </table>	gr. 80	50 ml	oz. 2.9	1.70 fl oz	<p>CDR.0864 Retaining+Sealant 83-21, high strength adhesive.</p> <p>For locking and sealing threads. Highly resistant to heat, corrosion, vibrations, water, gases, oils, hydrocarbons and many chemicals</p>  <table border="1"> <tr> <td>gr. 360</td> <td>250 ml</td> </tr> <tr> <td>oz. 12.7</td> <td>8.50 fl oz</td> </tr> </table>	gr. 360	250 ml	oz. 12.7	8.50 fl oz	<p>CDR.0854 Threadsealing 53-14, medium strength adhesive.</p> <p>For sealing hydraulic and pneumatics threads connectors up to 3/4". Highly resistant gases, water, LPG, hydrocarbons, oils and other chemicals</p>  <table border="1"> <tr> <td>gr. 80</td> <td>50 ml</td> </tr> <tr> <td>oz. 2.9</td> <td>1.70 fl oz</td> </tr> </table>	gr. 80	50 ml	oz. 2.9	1.70 fl oz	<p>CDR.0855 Threadsealing 53-14, medium strength adhesive.</p> <p>For sealing hydraulic and pneumatics threads connectors up to 3/4". Highly resistant gases, water, LPG, hydrocarbons, oils and other chemicals</p>  <table border="1"> <tr> <td>gr. 360</td> <td>250 ml</td> </tr> <tr> <td>oz. 12.7</td> <td>8.50 fl oz</td> </tr> </table>	gr. 360	250 ml	oz. 12.7	8.50 fl oz
gr. 360	250 ml																							
oz. 12.7	8.50 fl oz																							
gr. 80	50 ml																							
oz. 2.9	1.70 fl oz																							
gr. 360	250 ml																							
oz. 12.7	8.50 fl oz																							
gr. 80	50 ml																							
oz. 2.9	1.70 fl oz																							
gr. 360	250 ml																							
oz. 12.7	8.50 fl oz																							

<p>CDR.0856 Threadsealing 56-03, medium strength adhesive.</p> <p>For sealing hydraulic and pneumatics threads connectors up to 2". Highly resistant to heat, corrosion, shocks and vibrations</p>  <table border="1"> <tr> <td>gr. 360</td> <td>250 ml</td> </tr> <tr> <td>oz. 12.7</td> <td>8.50 fl oz</td> </tr> </table>	gr. 360	250 ml	oz. 12.7	8.50 fl oz	<p>CDR.0857 Threadsealing 85-86, high strength adhesive.</p> <p>For locking and sealing thread connections. Highly resistant to heat, corrosion, vibrations, water, gases, oils, hydrocarbons and many chemicals</p>  <table border="1"> <tr> <td>gr. 80</td> <td>50 ml</td> </tr> <tr> <td>oz. 2.9</td> <td>1.70 fl oz</td> </tr> </table>	gr. 80	50 ml	oz. 2.9	1.70 fl oz	<p>CDR.0858 Threadsealing 85-86, high strength adhesive.</p> <p>For locking and sealing thread connections. Highly resistant to heat, corrosion, vibrations, water, gases, oils, hydrocarbons and many chemicals</p>  <table border="1"> <tr> <td>gr. 360</td> <td>250 ml</td> </tr> <tr> <td>oz. 12.7</td> <td>8.50 fl oz</td> </tr> </table>	gr. 360	250 ml	oz. 12.7	8.50 fl oz	<p>CDR.1279 Threadsealing 18-10, high strength adhesive.</p> <p>Liquid teflon for sealing threaded metal joints. Suitable for sealing joints, used for: gas, LPG, drinking water, compressed air, oil and fuel, etc.</p>  <table border="1"> <tr> <td>gr. 100</td> <td>50 ml</td> </tr> <tr> <td>oz. 3.5</td> <td>1.70 fl oz</td> </tr> </table>	gr. 100	50 ml	oz. 3.5	1.70 fl oz	<p>CDR.1280 Threadsealing 18-10, high strength adhesive.</p> <p>Liquid teflon for sealing threaded metal joints. Suitable for sealing joints, used for: gas, LPG, drinking water, compressed air, oil and fuel, etc.</p>  <table border="1"> <tr> <td>gr. 430</td> <td>250 ml</td> </tr> <tr> <td>oz. 15.1</td> <td>8.50 fl oz</td> </tr> </table>	gr. 430	250 ml	oz. 15.1	8.50 fl oz
gr. 360	250 ml																							
oz. 12.7	8.50 fl oz																							
gr. 80	50 ml																							
oz. 2.9	1.70 fl oz																							
gr. 360	250 ml																							
oz. 12.7	8.50 fl oz																							
gr. 100	50 ml																							
oz. 3.5	1.70 fl oz																							
gr. 430	250 ml																							
oz. 15.1	8.50 fl oz																							

<p>CDR.1291 Polymer 400, lubricating mineral grease.</p> <p>With PTFE, resistant to stress and washing. Lubricates and protects against corrosion and ensures a long life for O-rings and seals</p>  <p>Not compatible with EPDM</p> <table border="1"> <tr> <td>gr. 40</td> <td>30 gr</td> </tr> <tr> <td>oz. 1.4</td> <td>1.05 oz.</td> </tr> </table>	gr. 40	30 gr	oz. 1.4	1.05 oz.	<p>CDR.1292 Polymer 400, lubricating mineral grease.</p> <p>With PTFE, resistant to stress and washing. Lubricates and protects against corrosion and ensures a long life for O-rings and seals</p>  <p>Not compatible with EPDM</p> <table border="1"> <tr> <td>gr. 140</td> <td>100 gr</td> </tr> <tr> <td>oz. 4.9</td> <td>3.50 oz.</td> </tr> </table>	gr. 140	100 gr	oz. 4.9	3.50 oz.	<p>CDR.1293 Silicon Comp 101/S, lubricating silicone grease</p> <p>With PTFE, for a better lubrication and sealing. Compatible with plastic, lubricates and protects against corrosion.</p>  <table border="1"> <tr> <td>gr. 40</td> <td>30 gr</td> </tr> <tr> <td>oz. 1.4</td> <td>1.05 oz.</td> </tr> </table>	gr. 40	30 gr	oz. 1.4	1.05 oz.	<p>CDR.1294 Silicon Comp 101/S, lubricating silicone grease</p> <p>With PTFE, for a better lubrication and sealing. Compatible with plastic, lubricates and protects against corrosion.</p>  <table border="1"> <tr> <td>gr. 140</td> <td>100 gr</td> </tr> <tr> <td>oz. 4.9</td> <td>3.50 oz.</td> </tr> </table>	gr. 140	100 gr	oz. 4.9	3.50 oz.	<p>GU.B20044 CdR 40 P.T.F.E., 12 m-39.40 ft length 12 mm-0.47" width</p>  <table border="1"> <tr> <td>gr. 20</td> <td></td> </tr> <tr> <td>oz. 0.7</td> <td></td> </tr> </table>	gr. 20		oz. 0.7	
gr. 40	30 gr																							
oz. 1.4	1.05 oz.																							
gr. 140	100 gr																							
oz. 4.9	3.50 oz.																							
gr. 40	30 gr																							
oz. 1.4	1.05 oz.																							
gr. 140	100 gr																							
oz. 4.9	3.50 oz.																							
gr. 20																								
oz. 0.7																								

<p>FB.0909 Antiscale solution, 10 Kg-22.07 lbs</p>  <table border="1"> <tr> <td>gr. 10150</td> <td></td> </tr> <tr> <td>oz. 358.3</td> <td></td> </tr> </table>	gr. 10150		oz. 358.3		<p>FB.0931 Descale solution, 10 Kg-22.07 lbs</p>  <table border="1"> <tr> <td>gr. 10150</td> <td></td> </tr> <tr> <td>oz. 358.3</td> <td></td> </tr> </table>	gr. 10150		oz. 358.3		<p>Cable-ties</p> 	<table border="1"> <thead> <tr> <th>Code</th> <th>Size</th> <th>Q.ty</th> <th>Weight</th> </tr> </thead> <tbody> <tr> <td>ZX.0212</td> <td>135x2,5 mm 5.32"x0.10"</td> <td>100 pcs</td> <td>gr. 40 oz. 1.5</td> </tr> <tr> <td>ZX.0213</td> <td>200x3,5 mm 7.88"x0.14"</td> <td>100 pcs</td> <td>gr. 90 oz. 3.2</td> </tr> <tr> <td>ZX.0214</td> <td>250x4,5 mm 9.85"x0.18"</td> <td>100 pcs</td> <td>gr. 180 oz. 6.4</td> </tr> <tr> <td>ZX.0215</td> <td>240x7,5 mm 9.46"x0.30"</td> <td>100 pcs</td> <td>gr. 370 oz. 13.1</td> </tr> <tr> <td>ZX.0216</td> <td>360x7,5 mm 14.18"x0.30"</td> <td>100 pcs</td> <td>gr. 530 oz. 18.8</td> </tr> </tbody> </table>	Code	Size	Q.ty	Weight	ZX.0212	135x2,5 mm 5.32"x0.10"	100 pcs	gr. 40 oz. 1.5	ZX.0213	200x3,5 mm 7.88"x0.14"	100 pcs	gr. 90 oz. 3.2	ZX.0214	250x4,5 mm 9.85"x0.18"	100 pcs	gr. 180 oz. 6.4	ZX.0215	240x7,5 mm 9.46"x0.30"	100 pcs	gr. 370 oz. 13.1	ZX.0216	360x7,5 mm 14.18"x0.30"	100 pcs	gr. 530 oz. 18.8
gr. 10150																																			
oz. 358.3																																			
gr. 10150																																			
oz. 358.3																																			
Code	Size	Q.ty	Weight																																
ZX.0212	135x2,5 mm 5.32"x0.10"	100 pcs	gr. 40 oz. 1.5																																
ZX.0213	200x3,5 mm 7.88"x0.14"	100 pcs	gr. 90 oz. 3.2																																
ZX.0214	250x4,5 mm 9.85"x0.18"	100 pcs	gr. 180 oz. 6.4																																
ZX.0215	240x7,5 mm 9.46"x0.30"	100 pcs	gr. 370 oz. 13.1																																
ZX.0216	360x7,5 mm 14.18"x0.30"	100 pcs	gr. 530 oz. 18.8																																